

SDI VIDEO 3006 CONNECTIONS BLACK EDITION

DIREKTRONIK

- Video SDI connection with cable Q11-3006N (0.8/3.75/6.0). Single strand Copper Wire 1/0.80mm, Black color. BNC SDI 4K in black with gold contacts.
- Flexible cable, with a resistant PVC jacket of Ø 6.00mm.
- Al Screen + Tinned Copper Braid 100% Coverage.
- Suitable for mobile applications and intensive work.

REFERENCES

Code	Length / Resolution	Packaging
EQ 3006N/0005N	0,5 m HD 3G 6G 12G	Bag
EQ 3006N/0010N	1 m HD 3G 6G 12G	Bag
EQ 3006N/0020N	2 m HD 3G 6G 12G	Bag
EQ 3006N/0030N	3 m HD 3G 6G 12G	Bag
EQ 3006N/0050N	5 m HD 3G 6G 12G	Bag
EQ 3006N/0070N	7 m HD 3G 6G 12G	Bag
EQ 3006N/0100N	10 m HD 3G 6G 12G	Bag
EQ 3006N/0150N	15 m HD 3G 6G 12G	Bag
EQ 3006N/0200N	20 m HD 3G 6G 12G	Bag
EQ 3006N/0250N	25 m HD 3G 6G 12G	Coiled
EQ 3006N/0300N	30 m HD 3G 6G 12G	Coiled
EQ 3006N/0400N	40 m HD 3G 6G 12G	Coiled
EQ 3006N/0500N	50 m HD 3G 6G 12G	Coiled
EQ 3006N/0600N	60 m HD 3G 6G	Coiled
EQ 3006N/0700N	70 m HD 3G 6G	Coiled
EQ 3006N/0800N	80 m HD 3G 6G	Coiled

DESCRIPTION

- Supported signals / Maximum length

HD-SDI 160 m 1080p 30fps (SMPTE 292M)
720p 60fps

3G-SDI / Full HD 120 m 1080p 60fps (SMPTE 424M)

6G-SDI / 4K-UHD 85 m 2160p 30fps (SMPTE 2081)

12G-SDI / 4K-UHD 55 m 2160p 60fps (SMPTE 2082)

- The single strand wire provides a high reliability in demanding environments.
- High signal propagation speed and low attenuation.
- High coverage double screen against external interferences.
- Minimal connector insertion loss due to gold-plated contacts.
- Clear sleeves on both ends for labeling.
- Emelec VíasCom strap to facilitate storage.
- Assembly carried out by experienced personnel and individually tested, ensuring a correct performance.



BNC SDI 4K



DIREKTRONIK