


















**Technische Daten / Specifications / Spécifications / Specifiche / Datos técnicos /
Technische gegevens / Tehniske data / Tekniska data / Technická data / Dane techniczne**

Item number	20117739	20117738
Connections	Euro plug (Type C, CEE 7/16), USB-C™ PD (Power Delivery) plug	
Input	220-240 V  , 50/60 Hz, 1.5 A max.	220-240 V  , 50/60 Hz, 1.8 A max.
Output	5.0 V  , 3.0 A, 15.0 W; 9.0 V  , 3.0 A, 27.0 W; 12.0 V  , 3.0 A, 36.0 W; 15.0 V  , 3.0 A, 45.0 W; 20.0 V  , 3.25 A, 65.0 W max.	5.0 V  , 3.0 A, 15.0 W; 9.0 V  , 3.0 A, 27.0 W; 12.0 V  , 3.0 A, 36.0 W; 15.0 V  , 3.0 A, 45.0 W; 20.0 V  , 4.5 A, 90.0 W max.
Total output	65.0 W max.	90.0 W max.
Average active efficiency	82.3 %	81.8 %
Efficiency at low load (10 %)	72.7 %	70.2 %
No-load power consumption	0.09 W	0.05 W
Max. operating temperature	25 °C	
Protection class	II 	
Protection against	short circuit, overcurrent, overvoltage and overheating	
Dimensions	88.8 x 76 x 29 mm	101.5 x 95 x 30 mm
Cable length	1.8 m	
Weight	approx. 159 g	approx. 258 g
Colour	black	

**Verwendete Symbole / Symbols used / Symboles utilisés / Simboli utilizzati / Símbolos utilizados /
Gebruikte symbolen / Brugte symboler / Använda symboler / Použité symboly / Stosowane symbole**

For indoor use only	IEC 60417- 5957	
Alternating current	IEC 60417- 5032	
Direct current	IEC 60417- 5031	
Class II equipment	IEC 60417- 5172	
Recycling	ISO 7001 - PI PF 066	