

USB 3.1 C Gen 2 to type C*2 port + USB3.1 Gen2 type A receptacle*2 port HUB

Specifications:

Upstream interface:	
Connector	USB 3.1 Gen2 type C receptacle connector
Cable	USB3.1 Gen2 type C plug to Type C plug cable
Downstream interface:	
Type C	USB3.1 Gen2 type C Receptacle Connector x 2
USB3.1 type A Port	USB 3.1 Gen2 type A Receptacle connector x2
Power :	
AC/DC Adapter	Input: AC 100-240V, 50~60 Hz Output: DC 5V/3.5A
DC DIM	or DC DIM : input DC voltage: 5V / current : 3.5A above
Power Mode	Self-Power
Functions :	
USB3.1 Gen2 type C and type A receptacle	*USB3.1 Gen2 type C and type A: 2*2 port (up to10Gbps) *support type C reversible plugging *support type C Locking connector

	<p>*support over-current protection</p> <p>*support LEDs indicate for downstream ports of device LINK</p> <p>*Supports USB Battery Charging V.1.2 (provide additional power of up to 2A for fast-charging an iPad®, smart phones, tablet or similar products.)</p>
Physical Specification :	
Dimensions	<p>Main body: 63.4(W)x24.6(H)x106.1 (D) mm</p> <p>Cable length: 60cm</p>
Weight	
Housing Material	metal

System Environments:

- * Microsoft Windows 7, 8, 8.1, 10 (32-bit or 64-bit) / LINUX / Mac OS compatible
- * CPU: Intel i3 Dual Core 1.5 GHz / Intel Atom "Bay Trail" Quad Core 1.33 GHz above
- * RAM: 2 GB or higher

Package :

- * USB 3.1 C Gen2 4 port HUB
- * USB 3.1 Gen2 type C cable
- * Power Adapter (5V/3.5A)

ID drawing :



DIREKTRONIK

Direktronik AB tel. 08-52 400 700 www.direktronik.se