

DVI Distributor, 25-0330 / 25-0332



Descriptions

The new DVI Distributor, 25-0330 or 25-0332 makes one(1) DVI video source split into four(4) or eight(8) DVI displays, respectively without any signal loss or digital noise. Also, HDMI source and displays are compatible by using HDMI-DVI cable.

Key Features

- Offers an **EDID** program feature
- Supports **DDC/HDCP**
- Supports up to **WUXGA (1920x1200)**, at 60Hz and HD 1080p (1920x1080).
- Provides **Power, Sync** LED indicators.
- Compatible with HDMI-DVI cable.

Technical Features

| Model Name | 25-0330 | 25-0332 |
|--------------------|-----------------------------|-------------------------|
| Input Signal | DVI (TMDS),Single Link | DVI (TMDS),Single Link |
| Output Signal | DVI Single Link , 4port, | DVI Single Link , 8port |
| Resolution | VGA to WUXGA, 480p to 1080p | |
| Receptacle | DC Power Jack DVI | |
| Power Supply | DC +5V , 2.6A | DC +5V , 3.0A |
| Dimension(mm) | 160 x 91 x 25 | 240 x 103 x 25 |
| Weight(kg) | 0.24 | 0.38 |
| Operating Temp. | 0°C~40°C | 0°C~48°C |
| Storage Temp. | -20°C~45°C | |
| Operating Humidity | 30%~80% | |
| Storage Humidity | 60% | |
| Power Consumption | 6W | 10W |